

Experience from the performance of ground improvement in thick marine clay deposit

by

Seung Ryull Kim, Dr. Eng., P.E.

President & CEO of the ESCO Engineers and Consultants Co. Ltd.

Contents



01 Introduction

02 Properties of subsoil Layers

03 Reclamation Fills

04 Ground Improvement Methods

05 Settlement Calculations

06 Field Observations

07 Concluding Remarks


Location of the Busan New Port




Close-up view of BNP site (from the satellite work)



Terminal and their related facility areas of BNP



Contents



01 Introduction

02 Properties of Subsoil Layers

03 Reclamation Fills

04 Ground Improvement Methods

05 Settlement Calculations


06 Field Observations

07 Concluding Remarks


Field and laboratory tests

Field Test	Quantity
Exploratory boring	257
CPT(piezococone)	84
Vane shear	108
Pressuremeter	18


Laboratory Test	Quantity
Natural moisture content	969
Sieve analysis	969
Atterberg limit	828
Consolidation	566
Unconfined compression	503
Triaxial compression	610



Deepest Bentonite layer (N<8)




Horizontal zoning Based on subsoil conditions




Container Terminal Area Terminal Related Facility Area

Profile of subsoil (section A-A)




Legend

- ① : Clay ($N < 8$)
- ② : Clay ($8 < N < 15$)
- ③ : Clay ($15 < N$)
- ④ : Sand & Gravel
- ⑤ : Bed Rock




Profile of subsoil (section B-B)




Legend

- ① : Clay ($N < 8$)
- ② : Clay ($8 < N < 15$)
- ③ : Clay ($15 < N$)
- ④ : Sand & Gravel
- ⑤ : Bed Rock




Plasticity chart & activity



Plasticity chart





Activity



Atterberg limits with depth


FA-2**CT-3**

Variation in water content and fine content


CT-2**FA-1**

Compression Indices with LL and e

Cc - LL




Cc - e




C_c values obtained from NCT & SCT sites


NCT+SCT




CT-2




FA-2




P_o' , P_c' and OCR values with depth




S_u obtained from different test devices




Variation of OCR, u , q_u and ϵ_f





q_u and axial strain in NCT & SCT regions



Relationship between q_u and N values





u/p_{on} vs. q/p relationship from N.C. Bangkok clay




(Kim, S.R., 1991)

u/p_{on} vs. q/p relationship from CKoU tests



Contents



01 Introduction

02 Properties of subsoil Layers

03 Reclamation Fills


04 Ground Improvement Methods

05 Settlement Calculations


06 Field Observations

07 Concluding Remarks


Typical section of BNP after reclamation




Grain size distribution of sand fill material




S_u of remolded clay with liquidity index




Settlement curves of clay particles with time



Effect of initial water content



Contents



01 Introduction

02 Properties of subsoil Layers

03 Reclamation Fills


04 Ground Improvement Methods

05 Settlement Calculations

06 Field Observations

07 Concluding Remarks


Design loads and allowable settlements



-  Container Terminal Area
-  Terminal Related Facility Area

Location	Operation load (kPa)	Allowable settlement (cm)
Container Terminal Area	30	10
Terminal Related Facility Area	15	30

Su & ω of dredged clay after application of PTM



(After Lee, Y.N. & Lee, S.W., 2003)

Onsite placement view of bamboo matting

■ Surface treatment method of dredged clay

