

Modelling of Shield Tunnels

Wout Broere



Section GeoEngineering




Delft University of Technology

Content

- Shield tunnel construction
 - Examples from the Netherlands
 - Results from research projects
- Modelling shield tunnels in Plaxis
 - Modelling in 2D
 - Modelling in 3D




Geology of the Netherlands



Geology of the Netherlands


Population Density in the Netherlands

- Less than 300 inhabitants per square kilometer
- Between 300 and 1000 inhabitants per square kilometer
- More than 1000 inhabitants per square kilometer



Types of soil in the Netherlands

- Loess landscape
- Dune landscape
- Sand landscape
- Seaclay landscape
- Riverclay landscape
- Peat landscape



Dutch Polders - Green Heart




Section GeoEngineering

TUDelft

Delft University of Technology

Green Heart Tunnel



Green Heart Tunnel



North-South Line



North-South Line

| | |
|----------------|--------|
| • Buiksloterm. | 22.500 |
| • v. Hasseltw. | 12.500 |
| • C.S. | 62.500 |
| • Rokin | 57.500 |
| • Vijzelgracht | 27.000 |
| • Ceintuurbn. | 35.000 |
| • Europapl. | 27.500 |
| • Zuid/WTC | 47.500 |




TU Delft

Delft University of Technology




Section GeoEngineering


Construction Methods





Depth of the Bored Tunnels





Deep Stations




City Surroundings




Emergency Exits




First FEM design efforts



Incorrect settlement profiles




Tunnel Boring Machine




zuidzijde

Noordzijde




Tunnel Face Stability



- Minimal and maximal support pressure
 - Pressure fluctuations
 - Limited fluctuations
 - Controlled process
 - Large fluctuations
 - Layer boundaries
 - Micro-instabilities
 - Clogging
 - Settlement control




Excess Pore Pressures




Forces in the Tunnel Lining



- Normal forces; peaks due to assembly
- Soil loading confirms
- Volume loss 0.5 %




Tangential Moments Influenced by Volume Loss




- Maximum bending moment occurs between 0.5 % and 1 % volume loss




Jack Forces



Figuur 1: De afzetcilinders van de Sophia-TBM, gezien in voorwaartse richting (VTR: Voorwaartse Richting).




Longitudinal Bending Moments





Analytical model

- Bending moments
- Weight TBM
- Bouyancy
- Soil support




Longitudinal Bending Moments




Tunnel Construction

1. Initial conditions
2. Excavation
 - Remove soil/water
 - Install TBM, conicity
 - Tail void
3. Lining installation
4. Grouting
5. Consolidation/creep




Tunnel Construction

- Activate shield
- Remove soil and water




Contraction

- Simulate (combined) effects of volume loss in a staged construction phase




Grout Pressure Modelling

- Simulate conicity and tail void by contraction
- Simulate grouting process (user defined pore pressure)
- Install lining




3DT modelling options





Construction Phases

- Geometry
 - TBM
 - Grout body
 - Final lining





Construction Phases

- Face support
 - Z-load in plane




Construction Phases

- Liquid Grout zone
 - User-defined pore pressure in cluster




Construction Phases


- Hardened Grout zone
 - Soil material with low stiffness
 - Final lining
- Jack forces



Close up



Close up



Copy option

Copy slice or plane [X]

Easy **Advanced**

Source segments

First
Plane ☒ ☐ Slice Front: Z = 0

Last
Plane ☒ ☐ Slice Front: Z = 0

Destination segments

First
Plane Front: Z = 0

Last
Plane Front: Z = 0

☐ **All plane data**

- ☐ **Pore pressures configuration**
 - ☐ User defined pressure distribution
 - ☐ Groundwater heads
- ☐ **Stresses and geometry configuration**
 - ☐ Z-Load properties
 - ☐ Distributed load B properties
 - ☐ Point load A properties
 - ☐ Tunnel contractions

☐ **All slice data**


- ☐ **Pore pressures configuration**
 - ☐ User defined pressure distribution
- ☐ **Stresses and geometry configuration**
 - ☐ Material sets for soil clusters
 - ☐ Material sets for structural elements (*)
 - ☐ Status of soil clusters
 - ☐ Status of structural elements (*)
 - ☐ Distributed load B properties
 - ☐ Point load A properties
 - ☐ Volumetric strains of clusters

(*) = plates



Copy Close



Step-wise excavation



Longitudinal Bending Moments




Example

- Second Heinenoord Tunnel (shield Tunnel)

| ID | Type | g_unsat | g_sat | nu | E_ref | c' | phi | psi | K0 |
|-----------|-----------|---------|---------|-------|---------|---------|-------|-------|------|
| | | [kN/m3] | [kN/m3] | [-] | [kN/m2] | [kN/m2] | [°] | [°] | [-] |
| 0B | Drained | 16.5 | 17.2 | 0.34 | 3900 | 3.0 | 27.0 | 0.0 | 0.58 |
| 0A | Undrained | 16.5 | 17.2 | 0.34 | 3900 | 3.0 | 27.0 | 0.0 | 0.58 |
| 3 | Drained | 19.5 | 19.5 | 0.30 | 19300 | 0.0 | 35.0 | 5.0 | 0.47 |
| 2 | Drained | 19.0 | 19.0 | 0.31 | 18500 | 0.0 | 33.0 | 3.0 | 0.47 |
| 18 | Drained | 20.5 | 20.5 | 0.30 | 29600 | 0.0 | 36.5 | 6.5 | 0.45 |
| 32 stiff | Drained | 20.5 | 20.5 | 0.30 | 444000 | 0.0 | 36.5 | 6.5 | 0.50 |
| 38 stiff | Undrained | 20.0 | 20.0 | 0.32 | 119000 | 7.0 | 31.0 | 1.0 | 0.55 |
| 38F stiff | Drained | 21.0 | 21.0 | 0.30 | 593000 | 0.0 | 37.5 | 7.5 | 0.56 |




Example



Example


- Phases:
 - TBM advances one slice (3m) in every phase
 - TBM front: face pressure
 - TBM tail: Contraction 0.5%
 - Between TBM and lining: Groutpressure, jack forces
 - Application of lining






Deformed mesh






Influence on pile foundation




22644 elements
61879 nodes
13 hours on PC




Phased simulation



Shaded deformations



Shear strains



Conclusions

- 3D calculations are time consuming, but become practically applicable.
- Perform 3D calculations only if really necessary
- Take care of the following aspects:
 - Choice of soil models and parameters
 - Mesh fineness (coarseness)
 - Calculation phases (construction stages)



β - Method

- Simulate spatial arching around tunnel
- NATM tunnelling

1. Generate initial conditions
2. Staged construction, using $\Sigma\text{-Mstage} = 1 - \beta$
3. Activate lining, continue s.c. to $\Sigma\text{-Mstage} = 1$

