

## LEAP-ASIA-2019: Validation of centrifuge experiments and generalized scaling law onliquefaction-induced lateral spreading

Tetsuo Tobita<sup>1</sup>, K. Ichii<sup>2</sup>, M. Okamura<sup>3</sup>, A.N. Sjafruddin<sup>3</sup>, J. Takemura<sup>4</sup>, L. Hang<sup>4</sup>, K.Ueda<sup>5</sup>, R. Uzuoka<sup>5</sup>, R.R. Vargas<sup>5</sup>, J. Boksmati<sup>6</sup>, A. Fusco<sup>6</sup>, S. Torres-Garcia<sup>6</sup>, S. Haigh<sup>6</sup>, G. Madabhushi<sup>6</sup>, M. Manzari<sup>7</sup>, S. Escoffier<sup>8</sup>, Z. Li<sup>8</sup>, D.S. Kim<sup>9</sup>, S. Manandhar<sup>9</sup>, W.-Y. Hung<sup>10</sup>, J.-X. Huang<sup>10</sup>, T.-N.-P. Pham<sup>10</sup>, M. Zeghal<sup>11</sup>, T. Abdoun<sup>11</sup>, E. Korre<sup>11</sup>, B.L. Kutter<sup>12</sup>, T.J. Carey<sup>12</sup>, N. Stone<sup>12</sup>, Y.-G. Zhou<sup>13</sup>, K. Liu<sup>13</sup>, and Q. Ma<sup>13</sup>

<sup>1</sup> Dept. of Civil, Environmental and Applied Systems Eng., Kansai University, 3-3-35, Yamate-cho, Suita, Osaka 564-8680, Japan.

<sup>2</sup> Faculty of Societal Safety Science, Kansai University, 7-1, Hakubai-cho, Takatsuki, Osaka 569-1098, Japan.

<sup>3</sup>Dept. of Civil and Environmental Engineering, Ehime University, 3 Bunkyo-cho, Matsuyama, 790-8577, Japan.

<sup>4</sup> Dept. of Civil and Environmental Eng., Tokyo Institute of Technology, 2-12-1, Ookayama, Meguro-ku, Tokyo, 152-8552, Japan.

<sup>5</sup>Disaster Prevention Research Institute, Kyoto University, Gokasho Uji 611-0011, Japan.

<sup>6</sup>Dept. of Engineering, Cambridge University, UK

<sup>7</sup>Dept. of Civil and Environmental Engineering, George Washington University, Washington DC, USA

<sup>8</sup>Dept. of Geotechnique Eau et Risques, IFSTTAR, Bouguenais, France

<sup>9</sup>Dept. of Civil and Environmental Engineering, Korean Advanced Institute of Science and Technology, KAIST, Republic of Korea

<sup>10</sup>Dept. of Civil Engineering, National Central University, Zhongli City, Taoyuan, Taiwan

<sup>11</sup>Dept. of Civil and Environmental Engineering, Rensselaer Polytechnic Institute, Troy, New York, USA

<sup>12</sup>Dept. of Civil and Environmental Engineering, University of California, Davis, USA

<sup>13</sup>Dept. of Civil Engineering, Institute of Geotechnical Engineering, Zhejiang University, Hangzhou 310058, P. R. China

**Keywords:**centrifuge; liquefaction; lateral spreading; scaling law; international collaboration project

LEAP (Liquefaction Experiment and AnalysisProject) is an international collaboration project aiming at validating both experimental and analytical methods to study liquefaction related phenomena. In addition to the goals set by the LEAP-UCD-2017 (Kutter et al., 2019), LEAP-ASIA-2019 aims at validating the generalized scaling law (hereafter “GSL”) (Iai et al., 2005) for the identical prototype with the one employed in UCD-2017. In ASIA-2019, 10 institutes conducted 23 tests in total.

The following is an excerpt from “LEAP-UCD-2017 Model Specifications” which also applies to the ASIA-2019. “The specific median soil deposit is a 4 m deep, 20 m long deposit of Ottawa F-65 sand with a dry density of 1,652 kg/m<sup>3</sup> and a ground slope of 5°. The specified median ground motion is a ramped sine wave input motion similar to the target motion for LEAP-GWU-2015 (Manzari et al. 2018). The primary response quantity of interest is the displacement and deformed shape of the soil deposit. Important secondary response quantities include time series data from acceleration, pore pressure, displacement sensors.”

Validation of the GSL can be done by the modeling of models technique, i.e., prototype behavior of Model A and Model B is examined. Execution of the following centrifuge model tests is requested for each institute:

Model A: A model identical to UCD-2017 (Fig. 1) whose response can be used to fill the gaps and further extend/establish/confirm the trends obtained in the UCD-2017 (Kutter et al. 2019).




Fig. 1. Baseline schematic for LEAP-ASIA-2019 experiment for shaking parallel to the axis of the centrifuge. (After Kutter et al. 2019)

Table 1 Scaling factors in physical model testing (Iai et al., 2005)

	(1) Scaling factors for 1g test	(2) Scaling factors for centrifuge test	(3) Generalized scaling factors
Length	$\mu$	$\eta$	$\mu\eta$
Density	1	1	1
Time	$\mu^{0.75}$	$\eta$	$\mu^{0.75}\eta$
Frequency	$\mu^{-0.75}$	$1/\eta$	$\mu^{-0.75}/\eta$
Acceleration	1	$1/\eta$	$1/\eta$
Velocity	$\mu^{0.75}$	1	$\mu^{0.75}$
Displacement	$\mu^{1.5}$	$\eta$	$\mu^{1.5}\eta$
Stress	$\mu$	1	$\mu$
Strain	$\mu^{0.5}$	1	$\mu^{0.5}$
Stiffness	$\mu^{0.5}$	1	$\mu^{0.5}$
Permeability	$\mu^{0.75}$	$\eta$	$\mu^{0.75}\eta$
Pore pressure	$\mu$	1	$\mu$

Model B: A model similar to Model A to validate the

GSL (Table 1). Upon constructing the model to be tested, only the viscosity of pore fluid and the input acceleration shall be scaled.

For each institute, the target relative density ( $D_r$ ) and peak amplitude of the input acceleration were assigned so that results were validated not by matching pinpoint but by the trend of output. As an input motion, the ramped sin wave (Fig. 2) was input which was evaluated by the effective PGA called  $PGA_{eff}$  (Kutter et al., 2019). Figure 3 shows covered range of the initial/input condition, i.e.,  $D_r$  and  $PGA_{eff}$  in both the UCD-2017 and ASIA-2019 series. In the latter series, having wider variation was intended, i.e.,  $PGA_{eff}$  varies from 0.1g to 0.4g. Achieved  $D_r$ , obtained by the established CPT correlation (Fig. 4), varies from 45% to 85%.

As an example, the measured accelerations are shown in Fig. 5, in which both model A and B show similar spiky responses due to dilation near the surface, which may validate the GSL on acceleration. As expected, when the ground is soft (CU, IFSTAR and ZJU), lateral displacements (Fig. 6) are larger (about 300 – 600 mm). In these cases, the observed differences among the corresponding responses measured for Model A and B are also larger. This may be indicating a limitation of the GSL and should be carefully examined in the future.




Fig. 2. Input base acceleration: Top) Isolated 1Hz signal, Mid) Isolated high frequency, and Bot) Achieved base motion (KyU-A1).




Fig. 3. Range of relative density and base excitation covered in LEAP-UCD-2017 and LEAP-ASIA-2019.




Fig. 4. Achieved relative density obtained from the CPT measurements.




Fig. 5. Comparison between Model A and B (KAIST).




Fig. 6 Measured surface lateral displacements.

## REFERENCES

- Iai, S., Tobita, T., and Nakahara, T. (2005). Generalized scaling relations for dynamic centrifuge tests, *Géotechnique*, 55(5), 355-362.
- Kutter, L. B., et al. (2019). LEAP-UCD-2017 V. 1.01 model specifications, Model tests and numerical simulations of liquefaction and lateral spreading: LEAP-UCD-2017, Ed. Kutter, Manzari and Zeghal, Springer, 625p. (in press).
- Manzari, T. M., et al. (2018). Liquefaction experiment and analysis projects (LEAP): Summary of observations from the planning phase, *Soil Dynamics and Earthquake Engineering*, LEAP2015 Special volume, Ed. Manzari, Kutter and Zeghal, 113, 714-743, DOI: 10.1016/j.soildyn.2017.05.015.